



Features and Benefits

- Provides up to 1.5% fuel economy improvement in tandem applications under newly revised SAE J1252 Wind Tunnel Test protocol
- Reduces aerodynamic drag between cab and trailer or between tandem trailers

Simple Installation

- Constructed in 3 sections to simplify installation and repair
- Designed for fast and easy installation and repair; installs in approximately 30 minutes
- Rivets directly to the nose of the trailer

Lightweight, Durable Design

- Impact and abrasion resistant – made with highly engineered TPO plastic for optimum flexibility, strength and durability

BASE SPECIFICATIONS

- 12”L x 92”W x 48”H
- Weight: 22 lbs
- Panel material: TPO plastic
- Color: White (custom colors available)
- Fits all dry van trailer makes and models
- Material is 100% recyclable and UV resistant



Impact and abrasion resistant – made with highly engineered TPO plastic for optimum flexibility, strength and durability



Designed for truckload (53') or less-than-truckload (LTL) applications

ORDERING INFORMATION

Call: 866-877-5062

Email: DuraPlate@wabashnational.com

Base specifications are accurate at the time of publication, and are subject to change without notice. Custom options are available; please consult your Wabash National representative for additional information. ©2017 Wabash National, L.P. All rights reserved. Wabash® and Wabash National® are marks owned by Wabash National, LP.



Wabash Composites

3000 East Main Street
Lafayette, IN 47905

wabashcomposites.com

DuraPlate@wabashnational.com

866-877-5062